

SKU: 584125

**Tecnodom**

**Refrigerated cabinet tropicalized Model  
AF07PKPLUSMBPV Stainless steel nevative  
temperature GN 2/1 with glass door**



## Descrizione

### Refrigerated Cabinet

#### Technical specifications

- Inside and outside in stainless steel, except bottom, ceiling and back in galvanized steel
- Internal rounded corners
- High pressure polyurethane injected without environmentally hazardous CFC gas
- Insulation thickness: 60 mm
- Self-closing door with magnetic seal. Thickness 60 mm. Reversible with special kit (Cod. KITREVPORPK on request)
- Front electronic control panel with 2 NTC probes for BT model
- Removable and tropicalised monobloc refrigerant unit as standard (ambient temperature +30 °C and relative humidity of 60%) operating with R290 gas
- Fan stop as standard
- Fully automatic defrosting and evaporation of condensate water
- Adjustable stainless steel feet (110/190 H mm)
- Ready-to-use

#### Standard equipment

- 3 hooks kit.
- 3 plastic coated grids GN 2/1.
- Fan stop.
- Door edge resistance
- 1 lock with key.
- 1 LED light board dashboard. The type of packaging includes shock-proof wooden support and plastic protections of the feet easy to remove.

### Scheda Tecnica

| Attributo       | Valore     |
|-----------------|------------|
| Altezza (cm)    | 203/210    |
| Capacità LT     | 700        |
| Lunghezza (cm)  | 71         |
| Profondità (cm) | 80         |
| Temperatura °C  | -22 / -18  |
| Tipologia Porte | Glass door |

| Attributo              | Valore               |
|------------------------|----------------------|
| Model Number for EPREL | AF07PKPLUSMBPV       |
| Temperatura            | Negative Temperature |